

flamex hybrid ®

Wherever there are welding chips and flying sparks, it is the flamex hybrid ® element

As the leading manufacturer in the field of flame retardant pneumatic hoses we developed the new *flamex*[®] due to market requirements.

flamex hybrid is a further development our product line **flamex** which is in use under heavy conditions for many years.

flamex hybrid *Phd- is the extreme resilient special tube out of polyurethane (PUR) for all applications in the field of welding machines, welding guns or flying sparks e.g. near grinder.

flamex hybrid **-hd- stand out for highest working pressure and extreme resilience in addition to the well known **flamex*** attributes.

flamex hybrid ** **-hd** is high tech ** Made in Germany* which is manufactured under highest quality standards due to a DIN EN ISO 9001:2000 certified Quality Management system.

Suitable for air, water and other liquid or gaseous medium Working pressure: -0,9 - 25 bar (depending on temperature)

- Extremely resistant against all kind of weld chips and flying sparks
- Maintenance rates could be extended in most cases
- Flame retarded without halogen, self-extinguishing in case of fire. Fire classification by Underwriters Laboratories Inc.®: listed UL 94 from V2 to V0
- Lower costs due to long durability
- Easy, quick and therefore cheap installation because there is no need for time-consuming dismantling of double-walled tube. No extra costs arise for special screw connectors.
- Suitable for all common instant plug-in connectors made out of metal or suitable plastics
- Resistant against microbes
- High chemical resistance (most detergents, solvents and other contact media)
- Small bend radius
- Excellent UV-resistance
- Top resistance to abrasion and scrubbing (suitable for drag chains)
- Free of substances retarding lacquer coverage
- High burst pressures
- Suitable for vacuum applications
- Recyclable (basic material could be reused), disposal permission as industrial waste similar to domestic waste
- Release to German automotive industry

The standard range contains the following dimensions:

_	
	DN
	2,00
	4,00
	6,00
	8,00
	10,00
	11,00

Other dimensions possible

This product line is available in the following colours:

black

Free of heavy metals | special colours possible

We deliver the tubing as rolls of 50 meters. The tubes can be ordered as single or multi tubes as well as spiral tubes.



Every inch a quality product

PAPUREX W. Büchner GmbH

Klein-Breitenbach 4a

D-69509 Mörlenbach Phone: +49 6209/279 Fax: +49 6209/46 27 E-Mail: info@papurex.de Internet: www.papurex.de